

## COMPREHENSIVE SERVICES

We offer competitive repair and calibration services, as well as easily accessible documentation and free downloadable resources.

## SELL YOUR SURPLUS

We buy new, used, decommissioned, and surplus parts from every NI series. We work out the best solution to suit your individual needs.

 Sell For Cash    Get Credit    Receive a Trade-In Deal

## OBSOLETE NI HARDWARE IN STOCK & READY TO SHIP

We stock **New, New Surplus, Refurbished, and Reconditioned** NI Hardware.



*Bridging the gap between the manufacturer and your legacy test system.*

 1-800-915-6216

 [www.apexwaves.com](http://www.apexwaves.com)

 [sales@apexwaves.com](mailto:sales@apexwaves.com)

*All trademarks, brands, and brand names are the property of their respective owners.*

**Request a Quote**

 **CLICK HERE**

**PXI-6533**

# NI 6533/6534 Specifications

This document lists features and specifications for the NI 6533/6534 family of devices and the NI PCI/PXI-7030/6533. The NI 6533/6534 family includes the following devices:

- NI PCI-6534
- NI PXI-6534
- NI PCI-6533 (PCI-DIO-32HS)
- NI PXI-6533
- NI DAQCard-6533
- NI AT-DIO-32HS



**Note** All NI 6533/6534 devices can be programmed with NI-DAQmx or NI-DAQ Traditional (Legacy), except for the NI DAQCard-6533 and NI AT-DIO-32HS, which are only supported with NI-DAQ Traditional (Legacy).

Specifications are typical at 25 °C unless otherwise noted. Specifications are subject to change without notice. For the most recent version of the specifications, visit [ni.com/manuals](http://ni.com/manuals).

## Digital I/O

---

Number of channels ..... 32 input/output;  
4 dedicated output and control;  
4 dedicated input and status

Compatibility ..... TTL/CMOS (standard or  
open collector)

Hysteresis ..... 500 mV

Digital logic levels

Level	Minimum	Maximum
Input low voltage	0 V	0.8 V
Input high voltage	2 V	5 V

Level	Minimum	Maximum
Input low current for data lines ( $V_{in} = 0.4\text{ V}$ ) DATA PULL <sup>†</sup> high DATA PULL low	— —	$-70\ \mu\text{A}$ $-10\ \mu\text{A}$
Input high current for data lines ( $V_{in} = 2.4\text{ V}$ ) DATA PULL high DATA PULL low	— —	$10\ \mu\text{A}$ $40\ \mu\text{A}$
Input low current for control lines ( $V_{in} = 0.4\text{ V}$ ) CTRL PULL <sup>‡</sup> high CTRL PULL low	— —	$-2.5\text{ mA}$ $-200\ \mu\text{A}$
Input high current for control lines ( $V_{in} = 2.4\text{ V}$ ) CTRL PULL high CTRL PULL low	— —	$200\ \mu\text{A}$ $1.4\text{ mA}$
Input low current for CTRL PULL/DATA PULL ( $V_{in} = 0.4\text{ V}$ )	—	$4\ \mu\text{A}$
Input high current for CTRL PULL/DATA PULL ( $V_{in} = 2.4\text{ V}$ )	—	$140\ \mu\text{A}$
Output low voltage ( $I_{OL} = 24\text{ mA}$ )	—	$0.4\text{ V}$
Output high voltage <sup>††</sup> ( $I_{OH} = 24\text{ mA}$ )	$2.4\text{ V}$	—
<sup>†</sup> DATA PULL is represented as the DPULL signal in Traditional NI-DAQ (Legacy). <sup>‡</sup> CTRL PULL is represented as the CPULL signal in Traditional NI-DAQ (Legacy). <sup>††</sup> When configured as active drive output terminals. Drivers configured for open-collector drive type are in the high-impedance state when at logic high level.		

**Absolute maximum**

input voltage range ..... $-0.3$  to  $5\text{ V}$

Power-on state for output channels .....High-impedance, pulled up  
or down (selectable)

Pull-up/down resistors

CTRL PULL (for control lines)..... $2.2\text{ k}\Omega$

DATA PULL (for data lines) ..... $100\text{ k}\Omega$

Data transfers (all devices

except NI DAQCard-6533).....Interrupt, DMA

# Memory

---

NI AT-DIO-32HS .....	16 S
NI DAQCard-6533 for PCMCIA.....	16 S
NI PCI/PXI-6534 .....	64 MB, two 32 MB modules on each NI 6534
NI PCI/PXI-7030/6533 .....	16 S
NI PCI-DIO-32HS .....	16 S
NI PXI-6533.....	16 S

# Sample Timing Types

---

## Sample Clock Timing<sup>1</sup>

Direction.....	Input or output
Maximum sample rate (internally timed, for small transfers <sup>2</sup> ).....	20 MHz
Minimum sample rate (internal clock rate) .....	1 S/10 minutes

## Change Detection

Change-detection resolution .....	150 ns
-----------------------------------	--------

# Triggers

---

## Start and Reference<sup>3</sup> Triggers

Compatibility .....	TTL/CMOS
Trigger types .....	Rising or falling edge, or digital pattern
Minimum pulse width for edge triggers .....	10 ns

---

<sup>1</sup> Sample clock timing is described as Pattern I/O in NI-DAQ Traditional (Legacy).

<sup>2</sup> Small transfer size is the size of the FIFO.

<sup>3</sup> Reference triggers are called Stop triggers in NI-DAQ Traditional (Legacy).

Pattern trigger detection capabilities .....	Detect pattern match or mismatch on user-selected data lines
Pattern trigger resolution .....	60 ns or one Sample clock <sup>1</sup> period, depending on pattern I/O mode

## RTSI Triggers (PCI, PXI, AT)

Trigger lines.....	7
--------------------	---

## Bus Interfaces

---

NI PCI-DIO-32HS/PXI-6533/ PCI-6534/PXI-6534.....	PCI master and target with onboard linking (scatter-gather) DMA
AT-DIO-32HS type .....	AT slave with dual DMA
NI DAQCard-6533 for PCMCIA type ...	PCMCIA slave

## Power

---

### Power Requirements

+5 VDC ( $\pm 5\%$ ) (with light output load)	
NI PCI-DIO-32HS, NI PXI-6533....	1.3 A
NI PCI-6534 and NI PXI-6534.....	2.0 A
NI DAQCard-6533 for PCMCIA ....	500 mA

### Power Available at I/O Connector

NI PCI-DIO-32HS, NI PXI-6533, NI AT-DIO-32HS, NI PCI-6534, and NI PXI-6534.....	+4.65 to +5.25 VDC at 1 A
NI DAQCard-6533 for PCMCIA .....	+4.65 to +5.25 VDC at 250 mA

---

<sup>1</sup> Sample clock is represented by the REQ signal in NI-DAQ Traditional (Legacy).

# Physical

---

## Dimensions, not including connectors

NI DAQCard-6533 for PCMCIA ...	8.6 by 5.3 cm (3.4 by 2.1 in.)
NI AT-DIO-32HS/ PCI-6533/6534 .....	17.5 by 10.7 cm (6.9 by 4.2 in.)
NI PXI-6533/6534 .....	16.3 by 9.9 cm (6.4 by 3.9 in.)

## I/O connector

NI PCI-DIO-32HS, NI PXI-6533, NI AT-DIO-32HS, NI PCI-6534, and NI PXI-6534 .....	68-pin male SCSI-II type
NI DAQCard-6533 for PCMCIA ...	68-pin female PCMCIA connector

# Environment

---

Operating temperature.....	0 to 55 °C
Storage temperature .....	-20 to 70 °C
Relative humidity .....	5 to 90% noncondensing
Functional shock .....	MIL-T-28800 E Class 3 (per Section 4.5.5.4.1) Half-sine shock pulse, 11 ms duration, 30 g peak, 30 shocks per face
Operational random vibration (PXI only) .....	5 to 500 Hz, 0.31 g <sub>rms</sub> , 3 axes
Nonoperational random vibration (PXI only) .....	5 to 500 Hz, 2.5 g <sub>rms</sub> , 3 axes



**Note** Random vibration profiles were developed in accordance with MIL-T-28800E and MIL-STD-810E Method 514. Test levels exceed those recommended in MIL-STD-810E for Category 1 (Basic Transportation, Figures 514.4-1 through 514.4-3).

National Instruments, NI, ni.com, and LabVIEW are trademarks of National Instruments Corporation. Refer to the *Terms of Use* section on [ni.com/legal](http://ni.com/legal) for more information about National Instruments trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering National Instruments products, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your CD, or [ni.com/patents](http://ni.com/patents).