

## COMPREHENSIVE SERVICES

We offer competitive repair and calibration services, as well as easily accessible documentation and free downloadable resources.

## SELL YOUR SURPLUS

We buy new, used, decommissioned, and surplus parts from every NI series. We work out the best solution to suit your individual needs.

 Sell For Cash    Get Credit    Receive a Trade-In Deal

## OBSOLETE NI HARDWARE IN STOCK & READY TO SHIP

We stock **New**, **New Surplus**, **Refurbished**, and **Reconditioned** NI Hardware.



*Bridging the gap between the manufacturer and your legacy test system.*

 1-800-915-6216

 [www.apexwaves.com](http://www.apexwaves.com)

 [sales@apexwaves.com](mailto:sales@apexwaves.com)

*All trademarks, brands, and brand names are the property of their respective owners.*

**Request a Quote**

 **CLICK HERE**

**PXI-8433-4**

# PXI-8432/4 and PXI-8433/4 Hardware Specifications

This document lists the specifications for the PXI-8432/4 and PXI-8433/4 boards.

## Environment

---

Maximum altitude ..... 2,000 m (at 25 °C ambient temperature)

Pollution Degree ..... 2

Indoor use only.

### Operating environment

Ambient temperature range ..... 0 to 55 °C (Tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.)

Relative humidity range ..... 10% to 90%, noncondensing (Tested in accordance with IEC-60068-2-56.)

### Storage environment

Ambient temperature range ..... -40 to 70 °C (Tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.)

Relative humidity range ..... 5% to 95%, noncondensing (Tested in accordance with IEC-60068-2-56.)

### Shock and vibration

Operational shock ..... 30 g peak, half-sin, 11 ms pulse (Tested in accordance with IEC-60068-2-27. Test profile developed in accordance with MIL-PRF-28800F.)

## Random vibration

Operating .....	5 to 500 Hz, 0.3 g <sub>rms</sub>
Nonoperating .....	5 to 500 Hz, 2.4 g <sub>rms</sub> (Tested in accordance with IEC-60068-2-64. Nonoperating test profile exceeds the requirements of MIL-PRF-28800F, Class 3.)

## Other Specifications

---

Dimensions .....16.0 × 10.0 cm (6.3 × 3.9 in.), 3U

IO connector .....10-position modular (RJ-50) x4

### Weight

PXI-8432/4 .....147 g

PXI-8433/4 .....147 g

### Power requirement (from PCI bus)

#### PXI-8432/4

+5 VDC .....925 mA typical  
2 A maximum

#### PXI-8433/4

+5 VDC .....950 mA typical  
2 A maximum

### Maximum serial transfer rate<sup>1</sup>

RS-485 .....3,000,000 bps

RS-232 .....1,000,000 bps

### Maximum cable length

RS-485<sup>2</sup> .....30 m (limited by EMC/surge)

RS-232 .....2,500 pF equivalent  
(TIA-EIA-232-F 2.1.4)

### Data line ESD protection (human body model)

RS-485 .....± 15 kV

RS-232 .....± 15 kV

---

<sup>1</sup> Actual speed may vary considerably from speed shown due to system and instrumentation capabilities.

<sup>2</sup> RS-485 is capable of 1.2 km (4,000 ft) without surge limitation.

# Safety

---

This product is designed to meet the requirements of the following standards of safety for information technology equipment:

- IEC 60950-1, EN 60950-1
- UL 60950-1
- CAN/CSA-C22.2 No. 60950-1



**Note** For UL and other safety certifications, refer to the product label or visit [ni.com/certification](http://ni.com/certification), search by model number or product line, and click the appropriate link in the Certification column.

# Electromagnetic Compatibility

---

Emissions ..... EN 55011 Class A at 10 m  
FCC Part 15A above 1 GHz

Immunity ..... EN 61326:1997 + A2:2001,  
Table 1

CE, C-Tick, and FCC Part 15 (Class A) Compliant.



**Note** For EMC compliance, operate this device with shielded cabling.

# CE Compliance

---

This product meets the essential requirements of applicable European Directives, as amended for CE marking, as follows:

Low-Voltage Directive (safety) ..... 73/23/EEC

Electromagnetic Compatibility  
Directive (EMC) ..... 89/336/EEC



**Note** Refer to the Declaration of Conformity (DoC) for this product for any additional regulatory compliance information. To obtain the DoC for this product, visit [ni.com/certification](http://ni.com/certification), search by model number or product line, and click the appropriate link in the Certification column.

National Instruments, NI, ni.com, and LabVIEW are trademarks of National Instruments Corporation. Refer to the *Terms of Use* section on [ni.com/legal](http://ni.com/legal) for more information about National Instruments trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering National Instruments products, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your CD, or [ni.com/patents](http://ni.com/patents).