

---

# PXle-5673E

# Specifications

---

2024-06-19



# Contents

NI PXIe-5673 Specifications ..... 3

# NI PXIe-5673 Specifications

## Specifications

This document lists specifications for the () RF vector signal generator. The RF vector signal generator is comprised of the I/Q modulator (), the arbitrary waveform generator (), and the RF signal generator () (used as an LO source). There is no single device labeled “.”

Specifications are warranted under the following conditions:

- minutes warm-up time
- Calibration adjustment cycle maintained
- Chassis fan speed set to High
- instrument driver self-calibration performed after instrument temperature is stable
- 50  $\Omega$  terminator connected to the LO OUT front panel connector
- onboard Reference Clock used as the Reference Clock
- in low loop bandwidth mode unless otherwise noted
- Most current product revision

**Specifications** describe the warranted, traceable product performance over ambient temperature ranges of 0 °C to 55 °C, unless otherwise noted.

**Typical** values describe useful product performance beyond specifications that are not covered by warranty and do not include guardbands for measurement uncertainty or drift. Typical values may not be verified on all units shipped from the factory. Unless otherwise noted, typical values cover the expected performance of units over ambient temperature ranges of 23 °C  $\pm$  5 °C with a 90% confidence level, based on measurements taken during development or production.

**Nominal** values (or supplemental information) describe additional information about the product that may be useful, including expected performance that is not covered under **Specifications** or **Typical** values. Nominal values are not covered by warranty.

Specifications are subject to change without notice. For the most recent device

specifications, visit [ni.com/manuals](http://ni.com/manuals).



**Caution** Refer to the ***Read Me First: Safety and Electromagnetic Compatibility*** document for important safety and electromagnetic compatibility information. To obtain a copy of this document online, visit [ni.com/manuals](http://ni.com/manuals) and search for the document title.



**Hot Surface** If the has been in use, it may exceed safe handling temperatures and cause burns. Allow the to cool before removing it from the chassis.



**Caution** The protection provided by this product may be impaired if it is used in a manner not described in this document.



**Caution** Electromagnetic interference can adversely affect the measurement accuracy of this product. The inputs and outputs of this device are not protected against electromagnetic interference for functional reasons. This product may experience reduced accuracy or other temporary performance degradation when cables are attached in an environment where electromagnetic interference is present.

## Frequency Characteristics

**Table 1.** Device Frequency Range

Frequency Range	NI 5673 Part Number
50 MHz to 1.3 GHz	780416-0x
50 MHz to 3.3 GHz	780417-0x
50 MHz to 6.6 GHz	780418-0x




**Note** NI 5673 part numbers vary according to memory size.

**Bandwidth**


Modulation bandwidth <sup>[1]</sup> (3 dB double sideband)	>100 MHz
--	----------

In the following three figures, measured modulation bandwidths show the actual baseband response. The usable bandwidth is limited by the I/Q generator sample rate from -80 MHz to 80 MHz. The shaded area between the solid lines indicates the frequency range covered by this specification.


**Figure 1. Measured Modulation Bandwidth at 1 GHz Carrier Frequency**



**Figure 2. Measured Modulation Bandwidth at 2.4 GHz Carrier Frequency**



**Figure 3. Measured Modulation Bandwidth at 5.8 GHz Carrier Frequency**



Data streaming continuous transfer rate	500 MB/s, nominal
---	-------------------

**Tuning Resolution ( )**

≤1.3 GHz	<1 Hz
>1.3 GHz to 3.3 GHz	<2 Hz
>3.3 GHz to 6.6 GHz	<4 Hz

**Frequency Settling Time<sup>[2],[3]</sup>**

**Table 2. Low Loop Bandwidth**

Frequency Settling Time	Median Tuning Speed (ms)	Maximum Tuning Speed (ms)
≤0.1 × 10 <sup>-6</sup> of final frequency	1.5	6.5
≤0.01 × 10 <sup>-6</sup> of final frequency	6.5	13

**Table 3.** High Loop Bandwidth

Frequency Settling Time	Median Tuning Speed (ms)	Maximum Tuning Speed (ms)
$\leq 1.0 \times 10^{-6}$ of final frequency	0.2	1.0
$\leq 0.1 \times 10^{-6}$ of final frequency	0.3	2.0
$\leq 0.01 \times 10^{-6}$ of final frequency	1.0	10.0

**Internal Frequency Reference ()**

Frequency	10 MHz
Initial accuracy	$\pm 3 \times 10^{-6}$
Temperature stability (15 °C to 35 °C)	$\pm 1 \times 10^{-6}$ , maximum
Aging per year	$\pm 5 \times 10^{-6}$ , maximum

**External Reference Input ()**

Frequency	10 MHz
Amplitude	1.0 V <sub>pk-pk</sub> to 5.0 V <sub>pk-pk</sub> into 50 $\Omega$ , nominal
Input impedance	50 $\Omega$
Coupling	AC

## External Reference Output ()

Frequency	10 MHz
10 MHz Reference Clock out	0.7 V <sub>pk-pk</sub> into 50 Ω, nominal
Output impedance	50 Ω
Coupling	AC

## Spectral Purity


Table 4. Single Sideband Phase Noise at 10 kHz Offset

Frequency	Phase Noise (dBc/Hz)
100 MHz	<-111, typical
500 MHz	<-107
1 GHz	<-105
2 GHz	<-98
3 GHz	<-95
4 GHz	<-93
5 GHz	<-90
6.6 GHz	<-84


High loop bandwidth has similar phase noise performance at 10 kHz offset, but this noise level extends to approximately 300 kHz offset before it starts rolling down at approximately 30 dB per decade until it reaches the far-out noise density.



**Figure 4.** Measured Phase Noise at 1 GHz, 2.4 GHz, and 5.8 GHz Using Internal 10 MHz Reference Clock




**Figure 5.** Measured Phase Noise at 5.8 GHz



Residual FM, 1 GHz (continuous wave, 300 Hz to 3 kHz integration bandwidth)	0.8 Hz RMS, typical
---	---------------------

**Figure 6. Phase Noise at 2.4 GHz in Low and High Loop Bandwidths**




## Spurious Responses

### Harmonics

Harmonics in the following table were measured using a 1 MHz baseband signal. The following specification includes all harmonic levels. Below 100 MHz, harmonic levels are nominally -11 dBc.

**Table 5. Harmonics**


Carrier Frequency	Specification (dBc)	Typical (dBc)
100 MHz to 250 MHz	-23	-30
>250 MHz to 1.3 GHz	-28	-35
>1.3 GHz to 3.3 GHz	-23	-30
>3.3 GHz to 6.6 GHz	-23	-28

Carrier Frequency	Specification (dBc)	Typical (dBc)
 <b>Note</b> Harmonic levels outside the device frequency range are typical.		

**Table 6.** Subharmonics and Non-Integer Harmonics

Carrier Frequency	Subharmonics <sup>[4]</sup>		Non-Integer Harmonics <sup>[5]</sup>	
	Specification (dBc)	Typical (dBc)	Specification (dBc)	Typical (dBc)
>3.3 GHz to 3.5 GHz	<-34	-41	<-41	-47
>3.5 GHz to 6.6 GHz	<-34	-41	<-46	-52


  

 <b>Note</b> Subharmonic and non-integer harmonic levels outside the device frequency range are typical.				
---	--	--	--	--

### Baseband Feedthrough

The measurement noise floor in the following figure is at -75 dBc. For example, with a baseband frequency of 10 MHz at an RF carrier frequency of 2 GHz, a 10 MHz signal is also present at the RF output at a level of -69 dBc.

**Figure 7.** Measured Baseband Feedthrough



## Baseband Image Feedthrough

Table 7. Typical Baseband Image Feedthrough<sup>[6]</sup>

I/Q Sample Rate	RF Bandwidth, 1 Sample per Symbol	Total Interpolation	Interpolated Sample Rate <sup>[7]</sup> (MS/s)	Image Feedthrough (dB), 20 MHz Bandwidth Signal	Image Feedthrough <sup>[8]</sup> (dB), Maximum I/Q Bandwidth
12 kS/s to 16.66 MS/s	9.6 kHz to 13.328 MHz	12 to 32,768 in steps of 8, 16, and 32	310 to 400	N/A	≤-100
16.66 MS/s to 33.33 MS/s	13.328 MHz to 26.664 MHz	12 to 24 in steps of 8	300 to 400	N/A	-88
33.33 MS/s to 50 MS/s	26.664 MHz to 40 MHz	8	267 to 400	N/A	-61
50 MS/s to 67.5 MS/s	40 MHz to 54 MHz	4	200 to 270	-31	-23
67.5 MS/s to 100 MS/s	54 MHz to 80 MHz	4	270 to 400	-62	-45
100 MS/s to 135 MS/s	80 MHz to 108 MHz	2	200 to 270	-31	-31
135 MS/s to 200 MS/s	108 MHz to 160 MHz	2	270 to 400	-62	-28
200 MS/s	108 MHz to 160 MHz	2	400	-82	-28


### Typical Modulation Spectrum

The following four figures indicate the achievable performance when you reduce the baseband power using prefilter gain.


The specifications in the following four figures were measured under the following conditions:

- Modulation: QPSK
- Symbol rate: 3.84 MS/s
- Filter: root raised cosine with alpha value of 0.22
- Filter length: 128 symbols
- RF power: set to -10 dBm
- Prefilter gain: set to -5 dB
- Number of averages by receiver: 100
- Noise cancellation: On


**Figure 8.** Measured Spectrum at 825 MHz




**Figure 9.** Measured Spectrum at 2.4 GHz



**Figure 10.** Measured Spectrum at 3.4 GHz



**Figure 11.** Measured Spectrum at 5.8 GHz**Output Intermodulation Distortion (IMD<sub>3</sub>) Products****Table 8.** Two Tones, 300 kHz Apart at -6 dBm per Tone


LO Frequency	Specification (dBc)	Typical (dBc)	Typical (dBc) -6 dB Prefilter Gain
85 MHz to 250 MHz	-49	-54	-62
>250 MHz to 1.3 GHz	-53	-57	-61
>1.3 GHz to 3.3 GHz	-48	-52	-56
>3.3 GHz to 6.6 GHz	-47	-50	-53

**Table 9.** Two Tones, 300 kHz Apart at -36 dBm per Tone

LO Frequency	Specification (dBc)	Typical (dBc)	Typical (dBc) -6 dB Prefilter Gain
85 MHz to 250 MHz	-51	-56	-62
>250 MHz to 1.3 GHz	-54	-59	-66
>1.3 GHz to 3.3 GHz	-50	-57	-62
>3.3 GHz to 6.6 GHz	-50	-57	-62

The IMD<sub>3</sub> specification is at full baseband power. IMD<sub>3</sub> performance can be improved by reducing the baseband level as shown in the previous four figures. When prefilter gain is reduced from full scale, the gain of the is adjusted to maintain the specified output power.

**Figure 12.** Measured IMD<sub>3</sub> Products




**Sideband Image Suppression**

**Table 10.** Sideband Image Suppression <sup>[9]</sup>

Frequency	2 MHz Modulation Bandwidth (dBc)	20 MHz Modulation Bandwidth (dBc)
85 MHz to 400 MHz	-43	-41
>400 MHz to 2.5 GHz	-50	-48
>2.5 GHz to 5.5 GHz	-46	-45
>5.5 GHz to 6.6 GHz	-43	-41

**Figure 13.** Measured Image Rejection Versus Baseband Frequency




**Carrier Suppression** <sup>[10]</sup>

85 MHz to 5.5 GHz	-44 dBc
>5.5 GHz to 6.6 GHz	-41 dBc



**Figure 14. Measured Carrier Suppression**



**Local Oscillator Feedthrough (Uncompensated)**

<3.3 GHz	-100 dBm, typical
≥3.3 GHz	-90 dBm, typical

**Baseband Linearity-Related Spurs (0 dBm RF OUT)**

85 MHz to 250 MHz	-51 dBc
>250 MHz to 6.6 GHz	-56 dBc

## RF Output Characteristics

### Power Range

Output <sup>[11]</sup>	Noise floor to +10 dBm, maximum
resolution	0.1 dB, minimum
	1 dB, typical
amplitude settling time <sup>[12]</sup>	<0.5 dB within 10 ms, typical

### Output Power Level Accuracy<sup>[13]</sup>

**Table 11.** Output Power Level Accuracy

Output Frequency	+5 dBm to -90 dBm	
85 MHz to 6.6 GHz	±0.75 dB (23 °C ± 5 °C)	±1.0 dB (0 °C to 55 °C)

**Table 12.** Nominal Output Power Level Accuracy at 23 °C ± 5 °C

Output Frequency	-10 dBm to +5 dBm	-50 dBm to -10 dBm
50 MHz to 85 MHz	±1.5 dB	±0.75 dB
>85 MHz to 100 MHz	±0.75 dB	±0.75 dB
>100 MHz to 5 GHz	±0.3 dB	±0.6 dB
>5 GHz to 6.6 GHz	±0.6 dB	±0.6 dB

### Output Noise Floor

**Table 13.** Specified and Typical RF Output Noise Floor

RF Output Power (dBm)	Specification ≤250 MHz	Specification >250 MHz	Typical ≤250 MHz	Typical >250 MHz
-30	-152 dBm/Hz	-152 dBm/Hz	-154 dBm/Hz	-154 dBm/Hz

RF Output Power (dBm)	Specification $\leq 250$ MHz	Specification $> 250$ MHz	Typical $\leq 250$ MHz	Typical $> 250$ MHz
-10	-145 dBm/Hz	-145 dBm/Hz	-148 dBm/Hz	-148 dBm/Hz
0	-140 dBm/Hz	-141 dBm/Hz	-142 dBm/Hz	-144 dBm/Hz
+10	-133 dBm/Hz	-134 dBm/Hz	-135 dBm/Hz	-136 dBm/Hz



**Note** Nominally, the noise floor drops 1 dB per dB of reduction in output power range.

### Voltage Standing Wave Ratio (VSWR)<sup>[14]</sup>

$< -10$ dBm output amplitude	$< 1.92:1$ , nominal
+10 dBm output amplitude	$< 2.2:1$ , nominal

### Phase Linearity

**Table 14.** Nominal Phase Linearity

Carrier Frequency	Modulation Bandwidth	Phase Linearity ( $^{\circ}$ )
85 MHz to 400 MHz	$\pm 10$ MHz (20 MHz bandwidth)	$\pm 1.0$
$> 400$ MHz to 6.6 GHz	$\pm 40$ MHz (80 MHz bandwidth)	$\pm 3.0$

### Pulse Modulation

Rise time	$< 5$ ns, typical
Fall time	$< 5$ ns, typical



**Note** Rise time and fall time is defined as 10% to 90%.

Pulse repetition frequency	50 MHz, maximum
Pulse delay (PLS MOD to RF OUT Connector)	10 ns, typical
Logic level	3.3 VTTL, nominal
PLS MOD input impedance	1 k $\Omega$ , nominal
<b>On/Off Ratio</b>	
<1 GHz	>50 dBc, typical
$\leq$ 3 GHz	>43 dBc, typical
$\leq$ 6.6 GHz	>30 dBc, typical

#### PXIe-5611 Front Panel Overload Protection

<b>Maximum reverse RF power</b>	
$\geq$ 4 GHz	1 W, maximum
<4 GHz	2 W, maximum
DC input	$\pm$ 5 VDC, maximum

## LO OUT on PXIe-5611 Front Panel Connector

Frequency range	50 MHz to 6.6 GHz
Power	0 dBm, $\pm 1.0$ dB, typical
Output power resolution	0.5 dB
Output impedance	50 $\Omega$ , nominal
<b>Output VSWR</b>	
50 MHz to 3.3 GHz	1.671:1, nominal
3.3 GHz to 4.8 GHz	2.100:1, nominal
4.8 GHz to 6.6 GHz	1.925:1, nominal
Amplitude settling time <sup>[15]</sup>	<0.5 dB in less than 10 ms, typical
I/Q inputs maximum RF power (each)	+19 dBm

**Table 15.** Typical Noise Figure<sup>[16]</sup>

Output Frequency (GHz)	Noise Figure (dB)
2	26
4	23
6	19

Maximum reverse power <sup>[17]</sup>	+18 dBm
Maximum saturated output power	+18 dBm
Maximum DC voltage	±5 VDC

#### LO OUT Isolation (State: Disabled)<sup>[18]</sup>

1 GHz	-50 dBc, typical
6.6 GHz	-30 dBc, typical

#### LO IN on PXIe-5611 Front Panel Connector

Frequency range	50 MHz to 6.6 GHz
Input power	0 dBm, nominal
Input impedance	50 $\Omega$ , nominal
Input VSWR	<2:1, nominal
Absolute maximum power	+18 dBm
Maximum DC power	±5 VDC

## Digital Modulation <sup>[19]</sup>

(Nominal)

**Table 23.** Quadrature Phase-Shift Keying (QPSK), Onboard Reference Clock Source

Symbol Rate (MS/s)	Bandwidth	Root Raised Cosine Filter Alpha Value	EVM (%)			MER (dB)		
			825 MHz	3,400 MHz	5,800 MHz	825 MHz	3,400 MHz	5,800 MHz
0.16	200.00 kHz	0.25	0.3	0.7	1.0	51	43	40
0.80	1.00 MHz	0.25	0.4	0.7	1.0	48	42	40
4.09	4.98 MHz	0.22	0.6	0.8	1.2	45	42	38

**Table 23.** QPSK, External Reference Clock Source (PXI Express Backplane Clock)

Symbol Rate (MS/s)	Bandwidth	Root Raised Cosine Filter Alpha Value	EVM (%)			MER (dB)		
			825 MHz	3,400 MHz	5,800 MHz	825 MHz	3,400 MHz	5,800 MHz
0.16	200.00 kHz	0.25	0.7	2	2.9	43	34	30
0.80	1.00 MHz	0.25	0.9	1.3	1.7	41	38	36
4.09	4.98 MHz	0.22	1.1	1.3	1.5	39	38	36

**Table 18.** 16-Quadrature Amplitude Modulation (QAM), Onboard Reference Clock Source

Symbol Rate (MS/s)	Bandwidth	Root Raised Cosine Filter Alpha Value	EVM (%)			MER (dB)		
			825 MHz	3,400 MHz	5,800 MHz	825 MHz	3,400 MHz	5,800 MHz
17.6	22 MHz	0.25	0.7	1.4	1.8	41	35	32
32.0	40 MHz	0.25	1.1	2.4	2.5	36	29	29

**Table 23.** 16-QAM, External Reference Clock Source (PXI Express Backplane Clock)

Symbol Rate (MS/s)	Bandwidth	Root Raised Cosine Filter Alpha Value	EVM (%)			MER (dB)		
			825 MHz	3,400 MHz	5,800 MHz	825 MHz	3,400 MHz	5,800 MHz
17.6	22 MHz	0.25	1	1.5	1.9	37	34	32
32.0	40 MHz	0.25	1.4	2.5	2.6	35	29	29

**Table 23.** 64-QAM, Onboard Reference Clock Source

Symbol Rate (MS/s)	Bandwidth	Root Raised Cosine Filter Alpha Value	EVM (%)			MER (dB)		
			825 MHz	3,400 MHz	5,800 MHz	825 MHz	3,400 MHz	5,800 MHz
5.36	6.16 MHz	0.15	0.4	0.6	1	44	40	37
6.95	7.99 MHz	0.15	0.5	0.7	1	43	39	36
40.99	50.00 MHz	0.22	1.3	2.8	2.6	34	27	28

**Table 23.** 64-QAM, External Reference Clock Source (PXI Express Backplane Clock)

Symbol Rate (MS/s)	Bandwidth	Root Raised Cosine Filter Alpha Value	EVM (%)			MER (dB)		
			825 MHz	3,400 MHz	5,800 MHz	825 MHz	3,400 MHz	5,800 MHz
5.36	6.16 MHz	0.15	0.9	1	1.2	38	36	35
6.95	7.99 MHz	0.15	0.9	1.1	1.2	38	36	35
40.99	50.00 MHz	0.22	1.5	2.8	2.7	33	27	28

**Table 23.** 256-QAM, Onboard Reference Clock Source

Symbol Rate (MS/s)	Bandwidth	Root Raised Cosine Filter Alpha Value	EVM (%)			MER (dB)		
			825 MHz	3,400 MHz	5,800 MHz	825 MHz	3,400 MHz	5,800 MHz
6.95	7.99 MHz	0.15	0.5	0.8	1.8	43	38	32




Table 23. 256-QAM, External Reference Clock Source (PXI Express Backplane Clock)

Symbol Rate (MS/s)	Bandwidth	Root Raised Cosine Filter Alpha Value	EVM (%)			MER (dB)		
			825 MHz	3,400 MHz	5,800 MHz	825 MHz	3,400 MHz	5,800 MHz
6.95	7.99 MHz	0.15	0.8	2	2.3	37	32	29

## Physical Characteristics

Figure 1. NI 5673 Front Panel



**Note** The NI 5611 front panel indicates the frequency range of warranted specifications.

## Front Panel Connector Types

<b>I/Q modulator module</b>	
I+	SMA female
I-	SMA female
Q+	SMA female
Q-	SMA female
RF OUT	SMA female
PLS MOD	SMA female
LO IN	SMA female
LO OUT	SMA female
<b>AWG module</b>	
CLK IN	SMA female
CLK OUT	SMA female
PFI 0	SMB

PFI 1	SMB
CH 0+/I+	SMA female
CH 0-/I-	SMA female
CH 1+/Q+	SMA female
CH 1-/Q-	SMA female
<b>LO source module</b>	
RF OUT	SMA female
REF IN/OUT	SMA female

## Dimensions and Weight

<b>Dimensions</b>	
	3U, One Slot, PXI Express module, 21.6 cm × 2.0 cm × 13.0 cm(8.5 in. × 0.8 in. × 5.1 in.)
	3U, Two Slot, PXI Express module, 21.6 cm × 4.0 cm × 13.0 cm(8.5 in. × 1.6 in. × 5.1 in.)
	3U, One Slot, module, 21.6 cm × 2.0 cm × 13.0 cm(8.5 in. × 0.8 in. × 5.1 in.)
<b>Weight</b>	

	567 g (20 oz)
	476 g (17 oz)
	415 g (15 oz)
(combined unit)	1,458 g (52 oz)



**Caution** Clean the hardware with a soft, nonmetallic brush. Make sure that the hardware is completely dry and free from contaminants before returning it to service.

## DC Power

Table 26. I/Q Modulator Module

Voltage (V <sub>DC</sub> )	Maximum Current (A)	Typical Current (A)
+3.3	0.6	0.6
+12.0	0.8	0.7



**Note** Power is 10.5 W, typical.

Table 26. AWG Module

Voltage (V <sub>DC</sub> )	Maximum Current (A)	Typical Current (A)
+3.3	2.0	1.9
+12.0	PXIe-5450: 2.5	PXIe-5450: 2.2
	PXIe-5451: 2.9	PXIe-5451: 2.6



Voltage (V <sub>DC</sub> )	Maximum Current (A)	Typical Current (A)
 <b>Note</b> Power is 32.7 W, typical (PXIe-5450); 37.5 W, typical (PXIe-5451).		

Table 26. NI PXI-5650/5651/5652 LO Source Module

Voltage (V <sub>DC</sub> )	Maximum Current (A)	Typical Current (A)
+3.3	1.0	0.9
+12.0	1.0	0.8
 <b>Note</b> Power is 12.6 W, typical.		

## Environment

Maximum altitude	2,000 m (800 mbar) (at 25 °C ambient temperature)
Pollution Degree	2

Indoor use only.

### Operating Environment

Ambient temperature range	0 °C to 55 °C
Relative humidity range	10% to 90%, noncondensing

## Storage Environment

Ambient temperature range	-40 °C to 71 °C
Relative humidity range	5% to 95%, noncondensing

## Shock and Vibration

Operating shock	30 g peak, half-sine, 11 ms pulse
<b>Random vibration</b>	
Operating	5 Hz to 500 Hz, 0.3 grms
Nonoperating	5 Hz to 500 Hz, 2.4 grms

## Calibration

<b>Recommended calibration interval</b>	
	1 year
	1 year
	1 year

## Compliance and Certifications

### Safety Compliance Standards

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA C22.2 No. 61010-1



**Note** For safety certifications, refer to the product label or the [Product Certifications and Declarations](#) section.

### Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions
- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



**Note** In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.



**Note** Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



**Note** For EMC declarations, certifications, and additional information, refer to the [Product Certifications and Declarations](#) section.

## Product Certifications and Declarations


Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit [ni.com/product-certifications](https://ni.com/product-certifications), search by model number, and click the appropriate link.

## Environmental Management


NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the ***Engineering a Healthy Planet*** web page at [ni.com/environment](https://ni.com/environment). This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

## EU and UK Customers

-  **Waste Electrical and Electronic Equipment (WEEE)**—At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit [ni.com/environment/weee](https://ni.com/environment/weee).

## 电子信息产品污染控制管理办法（中国RoHS）

-  **中国RoHS**—NI符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于NI中国RoHS合规性信息，请登录 [ni.com/environment/rohs\\_china](https://ni.com/environment/rohs_china)。(For information about China RoHS compliance, go to [ni.com/environment/rohs\\_china](https://ni.com/environment/rohs_china).)